

新品
推荐
NEW

S10



● 自主专利	Unique patented design
● 家用软水机定制阀的首选	Ideal for residential softener
● 软水溶盐	Soft water refill
● 顺逆流再生轻松转换	DF or UF regeneration easily converting in one unite
● 自带混水阀	Build in blended valve
● 独特专利设计的旁通阀	Unique patented bypass valve
● 备用电池断电时驱动控制阀到安全位置	Backup battery drive the control to the safty position when power off
● 自动报错提醒	Auto detect and alarm the system errors
● 自动维保提醒	Auto remind the periodic maintenance
● 假日模式	Holiday mode
● 密码保护	Password protection
● 先注水	Pre-refill
● 等比例再生	Proportional regeneration
● 控制阀历史使用数据查看	Diagnosis mode for checking the history data
● 可选安装福碧源公司的低盐报警控制器	Optional low salt sensor
● 预留树脂消毒装置控制接口	Optional chlorine producer control output interface
● 预留低盐报警控制接口	Optional low salt sensor control system input interface
● 预留远程信号控制输入接口	Optional DP switch with remote signal input interface
● 预留输出继电器控制接口	Optional AUX relay output interface

参数表 Specification

单阀流量 Flow rate (50PSI/3.5bar Valve only)	
连续供水 Continuous (15PSI/1bar drop)	2M ³ /H (9GPM)
峰值供水 Peak (25PSI/1.7bar drop)	2.7M ³ /H (12GPM)
峰值反洗 Max Backwash (25PSI/1.7bar drop)	0.7M ³ /H (3GPM)
工作CV值 (1PSI/0.07bar drop)	2.3
再生 Regeneration	
再生流向 UF/DF	DF & UF 顺流&逆流
阀位 Cycles	5
可调步序 Adjustable cycles	ALL 全部
再生周期时长 Time Available	0~999min
进出水 Inlet/Outlet	3/4", NPT or BSPT
底座 Base	2~1/2" 8NPSM
中心管 Distributor pilot	1.05", 26.7mm OD
排污口 Drain line	3/8" OD
吸盐口 Brine line	3/8" OD
灌口至顶部的高度 Height from top of tank	5.7"/143mm
重量 Weight	1.2KG
适用机型 Typical Application	软化 Softener 过滤 Filter
	6"-10" (150~250mm) 6"-9" (150~230mm)

