

Clack® 

WS1CI TWIN ALTERNATING CONTROL VALVE

WATER SPECIALIST CONTROL VALVE



- Service flow 106 lpm (6.36 m³/h) (28 gpm), backwash flow 57 lpm (3.40 m³/h) (15 gpm) with meter and bypass installed
- Solid state microprocessor with easy access front panel settings
- Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Program in ppm, French degrees, German degrees, or cubic meters
- Fully programmable regeneration cycle sequence (maximum 9)
- Programmable regeneration cycle times
- Days override feature; 1 – 28 days available
- Backwash and brining ability to 21" diameter tanks
- Downflow/upflow regeneration
- Stores system configuration and operation data in nonvolatile memory
- Coin Cell Lithium battery back-up with a 24 hour carry over
- 12-volt output AC Adapter provides safe and easy installation
- Control valve design provides optimum service and backwash rates
- Soft/treated water regeneration
- Pre or Post soft/treated water regenerant refill
- Low salt alarm
- 24-hour clock
- Patented one piece expanding seal spacer stack assembly U.S. Patent 6,402,944
- Patented linearly reciprocating piston operation U.S. Patent 6,444,127
- Reliable and proven DC drive

Water Specialist 1" CI Twin Alternating Specifications

Inlet/Outlet Fittings..... ¾" to 1.5" NPS
 Cycles up to 9
 Valve Material Noryl (1) or equivalent
 Regeneration downflow/upflow

FLOW RATES

Service @ 15 psi/1 bar drop (includes bypass and meter)..... 106 lpm (6.36 m³/h) (28 gpm)
 Backwash @ 25 psi/1.7 bar drop (includes bypass)..... 57 lpm (3.40 m³/h) (15 gpm)
 Cv Service 7.28
 Cv Backwash 2.96

OPERATING PRESSURES

Minimum/Maximum 20 - 125 psi (1.4 - 8.6 bar)

OPERATING TEMPERATURES

Minimum/Maximum 40° - 110° F (4° - 43° C)

METER

Accuracy ± 5%
 Flow Rate Range..... 0.95 - 102 lpm
 Volume Range 0.02 - 5,700 m³
 Totalizer 1 m³ - 99,999 m³

DIMENSIONS & WEIGHT

Distributor Pilot..... 1.050" OD Pipe (¾" NPS)
 Drain Line ¾" or 1" NPT
 Brine Line ⅜" or ½" OD Poly Tube Compression
 Mounting Base..... 2 ½" - 8 NPSM
 Height From Top Of Tank..... 7 ⅜" (187 mm)
 Weight 16 lbs (7.25 kg)

ELECTRICAL SPECIFICATIONS

AC Adapter

	<u>U.S.</u>	<u>International</u>
Supply Voltage	120V AC.....	230V AC
Supply Frequency	60 Hz.....	50 Hz
Output Voltage	12V AC.....	12V AC
Output Current	500 mA.....	500 mA

TANK APPLICATIONS

Water Softener 6" - 21" Diameter
 Water Filter (2) 6" - 21" Diameter

CYCLES OF OPERATION

Choose up to nine regeneration cycles, in any order, with a wide range of available values:

Cycle	Range of values
Backwash.....	1 - 120 minutes
Rinse.....	1 - 120 minutes
Pause (service).....	1 - 480 minutes
Brine (co-current).....	1 - 180 minutes
Brine (counter-current).....	1 - 180 minutes
Refill (softener)	0.05 - 95.00 Kg
Refill (filter)	0.05 - 95.00 Liters

Options: Backwash Filter, Bypass, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. Noryl is a trademark of Sabic Innovative Plastics IP B.V. Company
2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area/407 lpm per square meter of bed area