



## 6. Purificatoare pentru apa de la bucatarie prin Osmoza Inversa



Denumire	Purificator Aqua RO5	Pret lista [euro]
Cod	RO5	160
Dimensiuni [H x W x L]	450 x 150 x 450 mm	
Temperatura de lucru	2°C - 45°C	
Conexiune alimentare	1/2"	
Conexiune furtun	Quick conector alb	
Baterie	FXFCH5	
Presiune min/max	3-6 bar	
Set cartuse standard	F CPP10-5, FCCB10, F CPP10-1, TFC-50F, FCLCA	
Carcasa filtru	Polietilena	
Suport carcasa filtru	Polipropilena	
Numar O-ring	2	
Tanc de stocare	12 litri	
Dimensiuni tanc [H x D]	345 mm x 235 mm	

Sistemul include un set complet de cartuse, membrana osmotica, adaptori, baterie, cheie, tanc.



Denumire	Purificator Aqua RO5P	Pret lista [euro]
Cod	RO5P	240
Dimensiuni [H x W x L]	470 x 230 x 450 mm	
Temperatura de lucru	2°C - 45°C	
Conexiune alimentare	1/2"	
Conexiune furtun	Quick conector alb	
Baterie	FXFCH5	
Presiune min/max	1.5-6 bar	
Set cartuse standard	F CPP10-5, FCCB10, F CPP10-1, TFC-50F, FCLCA	
Carcasa filtru	Polietilena	
Suport carcasa filtru	Polipropilena	
Pompa Booster	Creste presiunea si volumul de apa produs.	
Tanc de stocare	12 litri	
Dimensiuni tanc [H x D]	345 mm x 235 mm	

Sistemul include un set complet de cartuse, membrana osmotica, adaptori, baterie, cheie, tanc.



Denumire	Purificator Aqua RO6M	Pret lista [euro]
Cod	RO6M	172
Dimensiuni [H x W x L]	450 x 150 x 450 mm	
Temperatura de lucru	2°C - 45°C	
Conexiune alimentare	1/2"	
Conexiune furtun	Quick conector alb	
Baterie	FXFCH4	
Presiune min/max	3-6 bar	
Set cartuse standard	F CPP10-5, FCCB10, F CPP10-1, TFC-50F, FCLCA, FCLRM	
Carcasa filtru	Polietilena	
Suport carcasa filtru	Polipropilena	
Numar O-ring	2	
Tanc de stocare	12 litri	
Dimensiuni tanc [H x D]	345 mm x 235 mm	

Sistemul include un set complet de cartuse, membrana osmotica, adaptori, **baterie dubla**, cheie, tanc.



Denumire	Purificator Aqua RO6PM	Pret lista [euro]
Cod	RO6PM	252
Dimensiuni [H x W x L]	470 x 230 x 450 mm	
Temperatura de lucru	2°C - 45°C	
Conexiune alimentare	1/2"	
Conexiune furtun	Quick conector alb	
Baterie	FXFCH4	
Presiune min/max	1.5-6 bar	
Set cartuse standard	F CPP10-5, FCCB10, F CPP10-1, TFC-50F, FCLCA, FCLRM	
Carcasa filtru	Polietilena	
Suport carcasa filtru	Polipropilena	
Pompa Booster	Creste presiunea si volumul de apa produs	
Tanc de stocare	12 litri	
Dimensiuni tanc [H x D]	345 mm x 235 mm	

Sistemul include un set complet de cartuse, membrana osmotica, adaptori, **baterie dubla**, cheie, tanc.



Denumire	Purificator Aqua RO6UV	Pret lista [euro]
Cod	RO6UV	246
Dimensiuni [H x W x L]	450 x 150 x 450 mm	
Temperatura de lucru	2°C - 45°C	
Conexiune alimentare	1/2"	
Conexiune furtun	Quick conector alb	
Baterie	FXFCH5	
Presiune min/max	3-6 bar	
Set cartuse standard	F CPP10-5, FCCB10, F CPP10-1,	
Carcasa filtru	TFC-50F, FCLCA	
Support carcasa filtru	Polietilena	
Sterilizator UV	AQS-1	
Tanc de stocare	12 litri	
Dimensiuni tanc [H x D]	345 mm x 235 mm	

Sistemul include un set complet de cartuse, membrana osmotica, adaptori, baterie, cheie, tanc.



Denumire	Purificator Aqua RO6PUV	Pret lista [euro]
Cod	RO6PUV	346
Dimensiuni [H x W x L]	470 x 230 x 450 mm	
Temperatura de lucru	2°C - 45°C	
Conexiune alimentare	1/2"	
Conexiune furtun	Quick conector alb	
Baterie	FXFCH5	
Presiune min/max	1.5-6 bar	
Set cartuse standard	F CPP10-5, FCCB10, F CPP10-1,	
Carcasa filtru	TFC-50F, FCLCA,	
Support carcasa filtru	Polietilena	
Sterilizator UV	AQS-1	
Pompa Booster	Creste presiunea si volumul de apa produs	
Tanc de stocare	12 litri	
Dimensiuni tanc [H x D]	345 mm x 235 mm	

Sistemul include un set complet de cartuse, membrana osmotica, adaptori, baterie, cheie, tanc



Denumire	Purificator Aqua RO7MUV	Pret lista [euro]
Cod	RO7MUV	265
Dimensiuni [H x W x L]	450 x 150 x 450 mm	
Temperatura de lucru	2°C - 45°C	
Conexiune alimentare	1/2"	
Conexiune furtun	Quick conector alb	
Baterie	FXFCH5	
Presiune min/max	3-6 bar	
Set cartuse standard	F CPP10-5, FCCB10, F CPP10-1,	
Carcasa filtru	TFC-50F, FCLCA, FCLRM,	
Support carcasa filtru	Polietilena	
Sterilizator UV	AQS-1	
Tanc de stocare	12 litri	
Dimensiuni tanc [H x D]	345 mm x 235 mm	

Sistemul include un set complet de cartuse, membrana osmotica, adaptori, cheie, tanc.



Denumire	Purificator Aqua RO7PMUV	Pret lista [euro]
Cod	RO7PMUV	376
Dimensiuni [H x W x L]	470 x 230 x 450 mm	
Temperatura de lucru	2°C - 45°C	
Conexiune alimentare	1/2"	
Conexiune furtun	Quick conector alb	
Baterie	FXFCH5	
Presiune min/max	1.5-6 bar	
Set cartuse standard	F CPP10-5, FCCB10, F CPP10-1,	
Carcasa filtru	TFC-75F, FCLCA, FCLRM,	
Support carcasa filtru	Polietilena	
Sterilizator UV	AQS-1	
Pompa Booster	Creste presiunea si volumul de apa produs	
Tanc de stocare	12 litri	
Dimensiuni tanc [H x D]	345 mm x 235 mm	

Sistemul include un set complet de cartuse, membrana osmotica, adaptori, cheie, tanc